

# Christie Boxer 4K20 and 4K30

		Christie Boxer 4K20 144-011103-01	Christie Boxer 4K30 144-001012-03
Image	brightness	<ul style="list-style-type: none"> <li>• 19,500 ANSI (typical)</li> <li>• 20,000 Center</li> <li>• 22,000 ISO</li> </ul>	<ul style="list-style-type: none"> <li>• 29,000 ANSI (typical)</li> <li>• 30,000 Center</li> <li>• 32,500 ISO</li> </ul>
	contrast	• 2000:1	
Display technology	type	• 3DLP® 1.38" DMD	
	native resolution	• 4K (4096 x 2160)	
Lamp	type	• 4 x 450W NSH	• 6 x 450W NSH
	life	• 1500 hrs to 70% initial brightness, and up to 2500 at 50%	
Inputs	standard	<ul style="list-style-type: none"> <li>• 1 x High bandwidth multi-input card (HBMIC)           <ul style="list-style-type: none"> <li>- 2 x 12G-SDI</li> <li>- 1 x HDMI 2.0</li> <li>- 1 x DisplayPort 1.2</li> <li>- 1 x Fiber (QSFP+) for use with Christie® Link Transmitter</li> <li>- HDBaseT</li> </ul> </li> </ul>	
Pixel clock		• 1.2Gpx/s - Christie TruLife Electronics	
Networking		<ul style="list-style-type: none"> <li>• Keypad</li> <li>• RS232 in</li> <li>• Ethernet (10/100) RJ45</li> </ul>	
Lens mount		<ul style="list-style-type: none"> <li>• Tool-free lens insertion system</li> <li>• Boresight adjustable</li> <li>• Motorized horizontal and vertical lens offset</li> <li>• Motorized zoom and focus adjustment</li> </ul>	
Lenses	fixed	<ul style="list-style-type: none"> <li>• 0.72:1 (no offset)</li> <li>• 0.9:1 (offset: V: ±45%, H: ±15%)</li> </ul>	
	zoom	<ul style="list-style-type: none"> <li>• 1.13-1.31:1 (offset: V: ±60%, H: 25%)</li> <li>• 1.31-1.63:1 (offset: V: ±80%, H: 30%)</li> <li>• 1.63-2.17:1 (offset: V: ±80%, H: 30%)</li> <li>• 1.99-2.71:1 (offset: V: ±15%, H: 5%)</li> <li>• 2.71-3.89:1 (offset: V: ±45%, H: 15%)</li> <li>• 3.89-5.43:1 (offset: V: ±85%, H: 25%)</li> <li>• 4.96:1-7.69:1 (offset: V: ±55%, H: 20%)</li> </ul>	
Optional accessories		<ul style="list-style-type: none"> <li>• Dual link DVI input card</li> <li>• Twin HDMI™ input card</li> <li>• Quad DisplayPort input card (slot 0 only)</li> <li>• Christie Link Transmitter (Fiber)</li> <li>• Dual 3G HD-SDI input card</li> <li>• Twin DisplayPort input card</li> <li>• Rigging and stacking frame</li> </ul>	
Power requirements	operating voltage	• 200-240V	
	operating current	• 19A	
Dimensions	size	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)	
	weight	• 160lbs (72.57kg)	
Operating environment	temperature	• 41-104°F (5-40°C)	
	humidity	• 10-80%, non-condensing	
Warranty		• Three years	

For Christie Boxer 2K20 and 2K30 specs, please visit [christiedigital.com](http://christiedigital.com).

## Corporate offices

Christie Digital Systems USA, Inc.  
Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Kitchener  
ph: 519 744 8005

## Worldwide offices

Australia ph: +61 (0) 7 3624 4888	Germany ph: +49 2161 664540	Republic of South Africa ph: +27 11 251 0000	United Kingdom ph: +44 (0) 118 977 8000
Brazil ph: +55 (11) 2548 4753	India ph: +91 (080) 6708 9999	Russian Federation and Eastern Europe ph: +36 (0) 1 47 48 100	United States (Arizona) ph: 602 943 5700
China (Beijing) ph: +86 10 6561 0240	Japan (Tokyo) ph: 81 3 3599 7481	Singapore ph: +65 6877 8737	United States (New York) ph: 646 779 2014
China (Shanghai) ph: +86 21 6278 7708	Korea (Seoul) ph: +82 2 702 1601	Spain ph: +34 91 633 9990	Independent sales consultant offices
France ph: +33 (0) 1 41 21 44 04	Mexico ph: +52 55-4744-1790	United Arab Emirates ph: +971 4 3206688	Italy ph: +39 (0) 2 9902 1161



For the most current specification information, please visit [www.christiedigital.com](http://christiedigital.com)

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

Printed in Canada on recycled paper. 4481 Mar 17

**CHRISTIE**®