CHRISTIE BOXER SERIES * UNDISPUTED PERFORMANCE *

STILL THE REIGNING CHAMP

Christie Boxer is the #1 selling high brightness projector over 28,000 lumens in the market¹





Christie Boxer Series

The Christie® Boxer Series of 3DLP® projectors represents the smartest, brightest and lightest high-performance, professional projectors available. Engineered, designed and built in our world-class facility, this series is the culmination of working closely with leading staging companies and AV professionals to understand their specific needs and expectations.

Weighing in at a svelte 160 lbs and including superior connectivity and a host of smart monitoring features, the Boxer Series packs a punch for high-impact visual events.

Pound-for-pound, the top performing projectors available

Christie TruLife™ electronics – a quantum leap in video-image processing, this platform forms the basis for the latest generation of projectors capable of delivering ultra-high resolution, high-frame-rate video with unprecedented image fidelity. The only electronics in the market to have 1.2Gps bandwidth ensuring high quality 4K signals aren't compromised by compression or the addition of artifacts due to inadequate processing.

Pixel perfect images – all the time. When we say 4K@60 and 4K@120 we mean true pixel perfect 4K (4096 x 2160) at the stated frame rate. No tricks. No scaling. No motion artifacts from pixel shifting and no edge enhancement artifacts. When applications require precise, accurate content, with high resolution and high frame rates, on a display larger than 100", nothing compares.

- > Native 4K DMD ensures every pixel gets perfectly replicated and displayed full time
- > Boxer 2K upscales content to be displayed on a 4K DMD which means 2K looks better

6 Mercury lamps designed for long life - 1500 hrs to 70%, 2500 hrs to 50% - Boxer's lamp tray system is designed to easily get you back to full brightness in minutes keeping Boxer looking as good as it did on Day 1.





Built with the user in mind

Short timelines, tight budgets and high expectations. AV professionals have enough to worry about - their projectors shouldn't be one of them. That's why we've optimized the Christie® Boxer to provide an exceptional and intuitive, profit-focused user experience.

- > Low cost of ownership
- > Low maintenance
- > Several models to choose from
- > Compact, lightweight and rugged
- > Smallest 30K projector on the market
- > 360-degree omnidirectional
- > Easy rigging and stacking
- > Near Field Communication (NFC) enabled
- > On-board toolkit

- > Low power preview mode
- > Accepts HDR10 signals
- > High bandwidth multi-input card (HBMIC)
- > Full bandwidth point-to-point fiber capabilities
- > AV system integration with Terra SDVoE input card
- > Built-in Christie Twist[™] image warping and blending software
- > Compatible with Christie Mystique™ Install
- > User-friendly interface



Superior connectivity

| | (&)) | Direc Fiber | | | |
|----------------------------------|---------------|----------------|--------------|--|----|
| | Boxer | Competitor A | Competitor B | | |
| Direct Fiber 40G (Christie Link) | Standard | | | | SI |
| SDVoE (Christie Terra) | Optional | | | | |
| 12G-SDI | Standard (x2) | | | | 1: |
| Multi 3G-SDI | Optional | Standard | Standard | | |
| DisplayPort 1.2 | Standard | Standard | | | D |
| Nulti-DisplayPort 1.1 | Optional | | | | |
| HDMI 2.0 | Standard | Standard | | | Н |
| Multi HDMI | Optional | | | | D |
| Multi DVI-D | Optional | | | | |
| HDBaseT™ | Standard | Standard | Standard | | Н |
| | | | | | |

Christie TruLife electronics platform

The Christie TruLife™ electronics platform is the basis for the latest generation of projectors capable of delivering ultra-high resolution, high-frame-rate video with unprecedented image fidelity. Leveraging the latest in FPGA integrated circuits and a proprietary floating point architecture (the equivalent of 25 bits fixed point processing resolution), Christie TruLife supports a videoprocessing pipeline of up to 1.2 Gigapixels per second (GPix/s), enabling the only 4K DLP® image processing at 120Hz – unmatched performance in the market. A standard feature on all 2K Boxer models, Christie TruLife Lite provides superior video processing for 2K and HD sources. Using the proprietary floating-point processing engine, Christie TruLife Lite provides increased dynamic range and superior scaling for an exceptional visual experience up to 60Hz performance.



Beyond the box

Christie Twist for warping and blending arrays

Manage arrayed projectors to display virtually any image, anywhere with Christie[®] Twist[™]. Christie Twist allows pixels to be mapped more easily onto any projection surface, maintaining proper geometry and accurate pixel-to-pixel alignment. The free software download controls image warping and blending for up to six Boxers in the same array. Optional Christie Twist Premium and Pro software support additional projector arrays and enhanced controls.





- Image on curved screen - without blending
- Curved screen - with blending

Perfectly aligned arrays. Automatically.

Christie Mystique™ Install eliminates the challenges and expertise needed to configure, align, blend and warp multi-projector arrays and complex screen setups. It includes advanced camera-based alignment and projection mapping calibration tools, software, hardware and services that significantly simplify these types of visual systems. Mystique Install includes Christie Guardian, an optional feature that monitors a blended projection system for any misalignment, automatically calibrating the image in real time, guickly, invisibly, and without interruption, even when content is playing.






Christie Virtual Remote - a versatile wireless projector control app

The Christie Virtual Remote app provides a Wi-Fi® projector control alternative for Android[™] smartphone or tablet which can be used anywhere, while maintaining all the capabilities of the standard IR remote. Users can scan for available projectors on the network to add them to a group, or manually type in the IP address of the desired projector.

High Bandwidth Multi-Input Card (HBMIC)

The High Bandwidth Multi-Input Card (HBMIC) is a standard on all Boxers and provides a wide selection of connections including two 12G-SDI inputs and allows for 4K@60Hz over a single cable. The HBMIC also adds direct fiber input capability for use with a Christie Link Transmitter (sold separately or as part of a bundle). All inputs offer preview capability and fast syncing or switching between inputs.




Christie Link transmitters let you go further

Simplify your setup, increase system reliability and go further with Christie Link onboard fiber input for direct point-to-point fiber connections supporting high quality 4K. Easily send high-bandwidth signals (up to 4K@120Hz) over long distances (up to 6.2 miles /10 km) directly into the projector on a single-fiber cable without latency or compression.

Designed to work perfectly with Christie Boxer projectors Christie Link can manage EDIDs throughout the entire system which helps ensure reliable performance.

Christie Terra do more with SDVoE AV over IP

Christie Terra is an AV over IP solution enabling the transport, processing and control of audio visual content using the Software Defined Video over Ethernet (SDVoE) standard. Terra comprises a Transmitter, Receiver and Controller. On the Boxer, the SDVoE input allows for direct interfacing of 4K AV content and control over 10G Ethernet for highly flexible, scalable and efficient AV system integration.








Not all 4K is equal

B 11 . Q 20 8 🚍


Some projectors use imagers with a lower native resolution and rely on optical actuators to rapidly shift pixels around on screen. This can trick the eye into thinking it's seeing a higher resolution image, but at any given time it is impossible to display the full 4K signal. While these pixel-shifting technologies try to mathematically preserve content, they ultimately can't and they introduce scaling artifacts and image manipulation. While these pixel-shifting solutions can be applicable for some applications where accurate 4K isn't mandatory, they can't deliver full 4K temporal resolution.


Native 4K (4096 x 2160) provides perfect pixel reproduction, addressing processing speeds up to 120Hz, with all pixels on the screen simultaneously in real time. When applications require precise, accurate content, with high resolution and high frame rates, on a display larger than 100", there's nothing better. Pixel shifted 4K (Shifted WUXGA - 1920 x 1200) 4M pixels






Native 4K 8.8M perfect pixels all the time





Pixel shifted 4K (Shifted WQXGA - 2560 x 1600) 8.3M interpolated pixels - time sequenced





Christie Boxer Series

| | | Christie Boxer 4K30 | Christie Boxer 4K20 |
|----------------|-------------|---|---|
| Image | brightness | Up to 32,500 ISO 30,000 Center 29,000 ANSI (typical) | Up to 22,000 ISO 20,000 Center 19,500 ANSI (typical) |
| | contrast | 2000:1 | 2000:1 |
| Display | technology | 3DLP 1.38" 4K DMD | 3DLP 1.38" 4K DMD |
| | resolution | 4K (4096 x 2160) | 4K (4096 x 2160) |
| Lamps | | 6 x 450W NSH | 4 x 450W NSH |
| Inputs | standard | 2 x 12G-SDI | 2 x 12G-SDI |
| | | 1 x HDMI 2.0 | 1 x HDMI 2.0 |
| | | 1 x DisplayPort 1.2 | 1 x DisplayPort 1.2 |
| • • | | 1 x Fiber (QSFP+) for use with Christie Link Transmitter | 1 x Fiber (QSFP+) for use with Christie Link Transmitter |
| | | HDBaseT | HDBaseT |
| | optional | Dual 3G SD/HD-SDI input card | Dual 3G SD/HD-SDI input card |
| | | Dual Link DVI input card | Dual Link DVI input card |
| Contra Manager | | High Bandwidth Multi-Input Card (HBMIC) | High Bandwidth Multi-Input Card (HBMIC) |
| | | Quad DisplayPort input card | Quad DisplayPort input card |
| | | Twin HDMI input card | Twin HDMI input card |
| | | Terra SDVoE input card | Terra SDVoE input card |
| | pixel clock | 1.2Gpx/s - Christie TruLife electronics | 1.2Gpx/s - Christie TruLife electronics |
| Physical | dimensions | (LxWxH) 36.77x23.39x12" (934x594x305mm) | (LxWxH) 36.77x23.39x12" (934x594x305mm) |
| | weight | 160lbs (72.57kg) | 160lbs (72.57kg) |
| dBA | | 49dBA | 49dBA |

Christie Mirage 304K Christie Boxer 2K30 Christie Boxer 2K20 Up to 32,500 ISO Up to 22,000 ISO 30,000 Center 29,000 ANSI (typical) 30,000 Center 20,000 Center 29,000 ANSI (typical) 19,500 ANSI (typical) 2000:1 2000:1 2000:1 3DLP 1.38" 4K DMD 3DLP 1.38" 4K DMD 3DLP 1.38" 4K DMD 4K (4096 x 2160) 2K (2048 x 1080) upscaled onto 4K DMD 2K (2048 x 1080) upscaled onto 4K DMD 6 x 450W NSH 6 x 450W NSH 4 x 450W NSH 4 x Twin DisplayPort input card 2 x 12G-SDI 2 x 12G-SDI HDBaseT 1 x HDMI 2.0 1 x HDMI 2.0 1 x DisplayPort 1.2 1 x DisplayPort 1.2 1 x Fiber (QSFP+) 1 x Fiber (QSFP+) for use with Christie Link Transmitter for use with Christie Link Transmitter HDBaseT HDBaseT Dual 3G SD/HD-SDI input card Dual 3G SD/HD-SDI input card Dual 3G SD/HD-SDI input card Dual Link DVI input card Dual Link DVI input card Dual Link DVI input card High Bandwidth Multi-Input Card (HBMIC) High Bandwidth Multi-Input Card (HBMIC) High Bandwidth Multi-Input Card (HBMIC) Quad DisplayPort input card Quad DisplayPort input card Quad DisplayPort input card Twin HDMI input card Twin HDMI input card Twin HDMI input card Terra SDVoE input card Terra SDVoE input card Terra SDVoE input card 1.2Gpx/s - Christie TruLife electronics 300 Mpx/s - Christie TruLife Lite electronics 300 Mpx/s - Christie TruLife Lite electronics (LxWxH) 36.77x23.39x12" (934x594x305mm) (LxWxH) 36.77x23.39x12" (934x594x305mm) (LxWxH) 36.77x23.39x12" (934x594x305mm) 160lbs (72.57kg) 160lbs (72.57kg) 160lbs (72.57kg) 49dBA 49dBA 49dBA

Particular level and level and

¹ Source: Future Source 2006-2017 quarter one

Corporate offices

Christie Digital Systems USA, Inc. Cypress ph: 714 236 8610

Christie Digital Systems Canada Inc. Kitchener ph: 519 744 8005

Independent sales consultant offices

ltaly ph: +39 (0) 2 9902 1161

Russia ph: +7 (495) 930 8961



Worldwide offices

Australia ph: +61 (0) 7 3624 4888 Brazil ph: +55 (11) 2548 4753 China (Beijing) ph: +86 10 6561 0240

China (Shanghai) ph: +86 21 6030 0500

Columbia ph: +57 (318) 447 3179

Eastern Europe ph: +36 (0)1 47 48 138

France ph: +33 (0) 1 41 21 44 04 Germany (Cologne) ph: +49 221 99 512-0 Germany (Moechengladbach) ph: +49 2161 566200

India ph: +91 (080) 6708 9999

Japan ph: +81 3 3599 7481

Mexico 147 3179 ph: +52 55 4744 1790

> Republic of South Africa ph: +27 11 251 0000

> > Singapore ph: +65 6877 8737

South Korea ph: +82 2 702 1601

Spain ph: +34 91 633 9990

United Arab Emirates ph: +971 (0) 4 503 6800

United Kingdom ph: +44 (0) 118 977 8000

United States (Arizona) ph: 602 943 5700

United States (New York) ph: 646 779 2014

For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001.
Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4698 May 18

