

Plixus V-IN

Plixus Video-IN Box



Description

The Plixus Video-IN Box is the perfect companion to insert any video stream anywhere on the Plixus® network.

Take presentations, recorded video from a camera or a video conference and make it available to any participant.

To ensure maximum compatibility options, the Plixus Video-IN Box comes equipped with multiple interfaces. It features 2 Plixus conference network ports, an HDMI in, dry contacts to request a video stream, and a dedicated video request slot. Consequently, it allows installers great flexibility.

Even mounting the unit is child's play: the Video-IN Box has VESA & DIN-rail mount options. Finally, it comes with the convenience of the Plixus architecture: a simple CAT 5e cable is all that is needed to connect it to the network.

Features & Benefits

- » Plug and play setup
- » Single CAT 5e cable suffices
- » Support for all formats up to 1080p/60
- » Transport lip-synced video with a delay fewer than a single frame
- » Effortless integration in Plixus network
- » Small footprint
- » VESA mount option
- » DIN-rail mount option

Connectivity

- » 2 Conference ports
- » 1 HDMI IN (with screw-lock)
- » Dry contacts
- » Video request slot
- » Plixus-powered

Accessories

A hardware video request button can be connected to the unit.

Plixus V-REQ

71.98.2921

Software

To fully configure, manage, and use the device, Televic's CoCon management software is required. The following standard license is required:

CoCon Video Routing **71.98.1113**

Specifications

Mechanical	
Material	Steel
Color	Tiger Carbon 01
Size (mm)	146 (w) × 26 (h) × 83 (d)
Size packed (mm)	To be determined
Weight	280
Weight packed	To be determined
Network Power Connector	
Voltage	48 VDC
Current consumption	0.15 A
Power consumption	6 W
Conference Network Ports	
Power over cable	48 VDC
Link speed	1000 Mbps