



High Brightness Short-Throw Projector

FEATURE

- Bright 3,300 ANSI lumens with a high 12,000:1 contrast ratio
- XGA resolution with a maximum resolution up to WUXGA
- Delivers a 77" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows a presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



The DX881ST is designed to cater for the education needs. The DX881ST delivers a 77" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,300 ANSI Lumens and contrast ratio of 12,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.

DX881ST

EDUCATION



SPECIFICATIONS



Display Type	Single 0.55" DLP Technology by TI
Brightness	3,300 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	12,000:1
Lamp Life and Type	3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn. Eco)
Throw Ratio	0.62
Image Size (Diagonal)	60" ~ 200"
Projection Distance	0.76 ~ 2.52
Projection Lens	F2.8, f7.26mm
Zoom Ratio	Fixed
Aspect Ratio	4:3 Native
Offset (full image height)	114% (full image height)
Keystone Correction	+/-40 Degree; +/- 40 Steps
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Lens Shift Range	n/a
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W (Mono)
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	314 x 216 x 126 mm
Weight	3.2kg
Noise Level	36dB/32dB (Normal/Eco. Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode)
Standard Warranty	3 years projector / 1 year on lamp or 1000 hours whichever comes first
Education Warranty	5 years projector / 3 years on lamp or 2000 hours whichever comes first
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp: 5811119560-SVV
UPC	814964 339836

© Copyright 2014 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands